


SITE LEVELS TO ARBITRARY DATUM.



(ii) Concrete pipes shall be spun by a centrifugal process or be vertically pressed. They shall possess self inverting sockets and shall comply with the requirements of and be tested in accordance with BS 5911:2002.

FOUL WATER	SURFACE WATER	
		PROPOSED DRAIN
		PROPOSED CULVERT DIVERSION
		PROPOSED SLOTTED PIPE WRAPPED IN GEOTEXTILE
		EXISTING DRAIN
		EXISTING DRAIN TO BE REMOVED
		PROPOSED TYPE 2 MH 1200mm
		PROPOSED TYPE 4 BRICK MH
		PROPOSED TYPE 3 INSPECTION CHAMBER 450mmØ / 600mmØ
		PROPOSED TYPE 4 INSPECTION CHAMBER 180mmØ / 250mmØ
		SOIL AND VENT PIPE
		RAIN WATER PIPE
		RODDING EYE
		PROPOSED THRESHOLD DRAIN
		SITE BOUNDARY
		PERMEABLE SURFACING
		2m CULVERT EASEMENT

PRELIMINARY DRAWING

NOT FOR CONSTRUCTION

HOP House, 41 Church Road
Hove, East Sussex BN3 2BE
www.hop.uk.com
ask@hop.uk.com
+44 (0)1273 223900

Rowing No.	Status
15718-HOP-ZZ-XX-DR-C-10001	S0
	Rev. P6

