WHY TREE PROTECTION IS NEEDED

1) Soil compaction kills roots - caused by plant movement and storage of materials within protected areas.
2) Trenching severs roots - many small roots grow within the top 600mm of soil. Even the removal of the top 200mm can cause damage.
3) Soil pollution kills roots - Dripping fuel storage or aerated washings can damage roots over long periods of time.
4) Altering soil levels kills roots - Raising the soil level can be used to increase levels can compact the underlying soil (see point 1). Lowering levels will remove roots causing damage to the tree.
5) Bark and branch damage - bark removal and branch damage can allow disease and fungi into the tree.

The impact of any of the above can take years to show- trees can have huge reserves of food and water.

LEGEND

TREE PROTECTION FENCING & EXCLUSION ZONE

All fencing shall be installed prior to any plant activity on site whatsoever, including demolition, utility installation, groundworks, and soil stripping.

Once erected all TPP will be regarded as sacrosanct, and will not be removed or altered without the written consent of the project arboriculturist and approval of the local planning authority. The TPP is suitable for the protection of retained trees on site, and is a rigid, interlocking vesi-mesh panels, well braced to resist impact by construction activities. Fixed to the ground by means of a scaffold framework that is set firmly into the ground. Should any alternative method of barrier construction be proposed, consultation with the project arboriculturist will be required to clarify the suitability of the proposal. Ground protection will be required where vehicular access is unavoidable (see detail). Once the exclusion zone has been protected by barriers and/or ground protection, construction can commence. All weather notices shall be erected on the barriers.



1 Standard scaffold poles
2 Heavy gauge 2 m tall galvanized tube and welded mesh infill panels
3 Panels secured to uprights and cross-members with wire ties
4 Ground level
5 Uprights driven into the ground until secure (minimum depth 0.6 m)
6 Braced scaffold clamps

SENSITIVE DEMOLITION

The existing features are within the RPAs of adjacent trees to be retained and therefore to minimise impact on underlying roots that are to be demolished as per the method statement & under the supervision of the project arboriculturist.

TREE TO BE RETAINED

TREE TO BE REMOVED

A CATEGORY TREE
B CATEGORY TREE
C CATEGORY TREE
R CATEGORY TREE

ROOT PROTECTION AREA (RPA) FOR RETAINED TREES

RESTRICTIONS WITHIN TREE PROTECTION AREAS

Inside the exclusion area of the fencing, the following shall apply:

- No mechanical excavation unless specified in writing.
- No changes in ground level except as may be approved under the supervision of the project arboriculturist.
- No trenching without a written method statement stating the exact approved by the project arboriculturist.
- No roots shall be severed for any purpose (except reversal of grass edging using hand tools).
- No storage of plant or materials.
- No fires shall be lit and any electrical installing (cement washings etc.).
- No vehicular access.
- No fixings.

In addition, the following restrictions are mandatory adjacent to trees:

- No substance (Cellular) is into earth, including fuels, oil, bitumen, cement (including cement washings), bulders sand, concrete mixing and other substances shall be discharged or dosed within or directly adjacent to the protection areas of retained trees.
- No fire shall be lit such that flames arise within 5m of tree foliage.

PHASING, SUPERVISION & INVENTORING OF DEVELOPMENT

Before any work starts on site, the tree protection measures shown on this plan are to be installed and a pre-start site meeting with the project arboriculturist, groundwork contractors, site manager and LPA arboriculturist officer/landscape officer held. Following this meeting, the tree protection measures shown are subject to monthly site monitoring visits from project arboriculturist.

Additional site supervision and input from the project arboriculturist is to occur:

1. Pre-start meeting with groundwork contractors, site manager and LPA arboricultural officer.
2. During the removal of existing stable blocks

Supervision is also required should any underlying access and/or must be located in the construction exclusion zone

The original of this drawing was produced in colour- a monochrome copy should not be relied upon.

0 5 10 15 20 25m

Rev	Date	Details	Drawn
D	07/07/14	Amended site layout	AJB
C	24/04/14	Amended site layout	AJB
B	28/03/14	Amended site layout	AJB
A	20/02/14	Amended site layout	AJB

ACD
Ecology
Arboriculture
Landscape Architecture
Southorme Hall Business Centre, Grange Lane, Malmesbury, Wilts, SN16 0ES
Tel: 01666 826646 Fax: 01666 826654
Tanners, Lower Street, Haslemere, Surrey, GU27 2PE
Tel: 01483 423714 Fax: 01428 641160
12 Southgate Street, Winchester, Hampshire, SO23 9EF
Tel: 01962 855634
www.acdlandscape.co.uk

Copyright of ACD. All rights described in Chapter IV of the Copyright, Designs and Patents Act 1988 are hereby asserted. 2011. Copyright of this plan remains with ACD until all fees have been paid in full.

DAVID WILSON HOMES

scheme: Land at Roundstone, Angmering
client: David Wilson Homes

drawing: Tree Protection Plan
date: July 2012
scale: 1:500@A0
dwg no: BSH17576-03C
drawn: AJB checked: MW