

The Civil Engineering Practice		Page 1
11 Tungsten Building George Street Fishersgate BN41 1RA	Manor Nursery Angmering West Sussex	
Date 28/06/2019	Designed by S Burgess	
File Planning Network File.MDX	Checked by SRD	
Innovyze	Network 2020.1	

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for NETWORK 1.SWS

Pipe Sizes NETWORK 9 Manhole Sizes NETWORK 9

FSR Rainfall Model - England and Wales

Return Period (years)	2	PIMP (%)	100
M5-60 (mm)	19.600	Add Flow / Climate Change (%)	0
Ratio R	0.350	Minimum Backdrop Height (m)	0.500
Maximum Rainfall (mm/hr)	50	Maximum Backdrop Height (m)	1.000
Maximum Time of Concentration (mins)	30	Min Design Depth for Optimisation (m)	1.200
Foul Sewage (l/s/ha)	0.000	Min Vel for Auto Design only (m/s)	0.75
Volumetric Runoff Coeff.	0.750	Min Slope for Optimisation (1:X)	500

Designed with Level Soffits

Time Area Diagram for NETWORK 1.SWS

Time (mins)	Area (ha)	Time (mins)	Area (ha)
0-4	0.119	4-8	0.038

Total Area Contributing (ha) = 0.157

Total Pipe Volume (m³) = 1.865

Network Design Table for NETWORK 1.SWS

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design
1.000	20.697	0.230	90.0	0.019	5.00	0.0	0.600	o	100	Pipe/Conduit	
1.001	6.648	0.077	86.3	0.000	0.00	0.0	0.600	o	100	Pipe/Conduit	
1.002	6.073	0.374	16.2	0.012	0.00	0.0	0.600	o	100	Pipe/Conduit	
2.000	8.048	0.365	22.1	0.016	5.00	0.0	0.600	o	100	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	E I.Area (ha)	E Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.000	50.00	5.43	15.366	0.019	0.0	0.0	0.0	0.81	6.4	2.6
1.001	50.00	5.56	15.136	0.019	0.0	0.0	0.0	0.83	6.5	2.6
1.002	50.00	5.61	15.059	0.031	0.0	0.0	0.0	1.93	15.1	4.2
2.000	50.00	5.08	15.050	0.016	0.0	0.0	0.0	1.65	13.0	2.2

©1982-2020 Innovyze

The Civil Engineering Practice											Page 2																																																																																																																																																																																																																																																												
11 Tungsten Building George Street Fishersgate BN41 1RA						Manor Nursery Angmering West Sussex																																																																																																																																																																																																																																																																	
Date 28/06/2019						Designed by S Burgess																																																																																																																																																																																																																																																																	
File Planning Network File.MDX						Checked by SRD																																																																																																																																																																																																																																																																	
Innovyze						Network 2020.1																																																																																																																																																																																																																																																																	
<u>Network Design Table for NETWORK 1.SWS</u> <table><tr><th>PN</th><th>Length (m)</th><th>Fall (m)</th><th>Slope (1:X)</th><th>I.Area (ha)</th><th>T.E. (mins)</th><th>Base Flow (l/s)</th><th>k (mm)</th><th>HYD SECT</th><th>DIA (mm)</th><th>Section Type</th><th>Auto Design</th></tr><tr><td>1.003</td><td>13.287</td><td>0.149</td><td>89.2</td><td>0.005</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>150</td><td>Pipe/Conduit</td><td></td></tr><tr><td>1.004</td><td>20.099</td><td>0.115</td><td>174.8</td><td>0.029</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>150</td><td>Pipe/Conduit</td><td></td></tr><tr><td>3.000</td><td>15.482</td><td>0.262</td><td>59.0</td><td>0.020</td><td>5.00</td><td>0.0</td><td>0.600</td><td>o</td><td>100</td><td>Pipe/Conduit</td><td></td></tr><tr><td>3.001</td><td>9.676</td><td>0.094</td><td>103.4</td><td>0.007</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>100</td><td>Pipe/Conduit</td><td></td></tr><tr><td>4.000</td><td>11.118</td><td>0.692</td><td>16.1</td><td>0.014</td><td>5.00</td><td>0.0</td><td>0.600</td><td>o</td><td>100</td><td>Pipe/Conduit</td><td></td></tr><tr><td>3.002</td><td>25.581</td><td>0.243</td><td>105.3</td><td>0.015</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>150</td><td>Pipe/Conduit</td><td></td></tr><tr><td>3.003</td><td>2.503</td><td>0.087</td><td>28.8</td><td>0.012</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>150</td><td>Pipe/Conduit</td><td></td></tr><tr><td>1.005</td><td>4.226</td><td>0.024</td><td>176.1</td><td>0.008</td><td>0.00</td><td>0.0</td><td>0.600</td><td>o</td><td>225</td><td>Pipe/Conduit</td><td></td></tr></table> <u>Network Results Table</u> <table><tr><th>PN</th><th>Rain (mm/hr)</th><th>T.C. (mins)</th><th>US/IL (m)</th><th>Σ I.Area (ha)</th><th>Σ Base Flow (l/s)</th><th>Foul (l/s)</th><th>Add Flow (l/s)</th><th>Vel (m/s)</th><th>Cap (l/s)</th><th>Flow (l/s)</th></tr><tr><td>1.003</td><td>50.00</td><td>5.82</td><td>14.635</td><td>0.052</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.06</td><td>18.8</td><td>7.0</td></tr><tr><td>1.004</td><td>50.00</td><td>6.26</td><td>14.486</td><td>0.081</td><td>0.0</td><td>0.0</td><td>0.0</td><td>0.76</td><td>13.4</td><td>11.0</td></tr><tr><td>3.000</td><td>50.00</td><td>5.26</td><td>14.189</td><td>0.020</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.00</td><td>7.9</td><td>2.7</td></tr><tr><td>3.001</td><td>50.00</td><td>5.47</td><td>13.927</td><td>0.027</td><td>0.0</td><td>0.0</td><td>0.0</td><td>0.76</td><td>5.9</td><td>3.7</td></tr><tr><td>4.000</td><td>50.00</td><td>5.10</td><td>14.525</td><td>0.014</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.94</td><td>15.2</td><td>1.9</td></tr><tr><td>3.002</td><td>50.00</td><td>5.91</td><td>13.783</td><td>0.056</td><td>0.0</td><td>0.0</td><td>0.0</td><td>0.98</td><td>17.3</td><td>7.6</td></tr><tr><td>3.003</td><td>50.00</td><td>5.93</td><td>13.540</td><td>0.068</td><td>0.0</td><td>0.0</td><td>0.0</td><td>1.88</td><td>33.3</td><td>9.2</td></tr><tr><td>1.005</td><td>50.00</td><td>6.33</td><td>13.378</td><td>0.157</td><td>0.0</td><td>0.0</td><td>0.0</td><td>0.98</td><td>39.1</td><td>21.3</td></tr></table> <u>Simulation Criteria for NETWORK 1.SWS</u> <table><tr><td>Volumetric Runoff Coeff</td><td>0.750</td><td>Additional Flow - % of Total Flow</td><td>0.000</td></tr><tr><td>Areal Reduction Factor</td><td>1.000</td><td>MADD Factor * 10m³/ha Storage</td><td>2.000</td></tr><tr><td>Hot Start (mins)</td><td>0</td><td>Inlet Coefficient</td><td>0.800</td></tr><tr><td>Hot Start Level (mm)</td><td>0</td><td>Flow per Person per Day (l/per/day)</td><td>0.000</td></tr><tr><td>Manhole Headloss Coeff (Global)</td><td>0.500</td><td>Run Time (mins)</td><td>60</td></tr><tr><td>Foul Sewage per hectare (l/s)</td><td>0.000</td><td>Output Interval (mins)</td><td>1</td></tr><tr><td>Number of Input Hydrographs</td><td>0</td><td>Number of Storage Structures</td><td>0</td></tr><tr><td>Number of Online Controls</td><td>0</td><td>Number of Time/Area Diagrams</td><td>0</td></tr><tr><td>Number of Offline Controls</td><td>0</td><td>Number of Real Time Controls</td><td>0</td></tr></table> <u>Synthetic Rainfall Details</u> <table><tr><td>Rainfall Model</td><td>FSR</td><td>Region</td><td>England and Wales</td></tr><tr><td>Return Period (years)</td><td>2</td><td>M5-60 (mm)</td><td>19.500</td></tr></table>													PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design	1.003	13.287	0.149	89.2	0.005	0.00	0.0	0.600	o	150	Pipe/Conduit		1.004	20.099	0.115	174.8	0.029	0.00	0.0	0.600	o	150	Pipe/Conduit		3.000	15.482	0.262	59.0	0.020	5.00	0.0	0.600	o	100	Pipe/Conduit		3.001	9.676	0.094	103.4	0.007	0.00	0.0	0.600	o	100	Pipe/Conduit		4.000	11.118	0.692	16.1	0.014	5.00	0.0	0.600	o	100	Pipe/Conduit		3.002	25.581	0.243	105.3	0.015	0.00	0.0	0.600	o	150	Pipe/Conduit		3.003	2.503	0.087	28.8	0.012	0.00	0.0	0.600	o	150	Pipe/Conduit		1.005	4.226	0.024	176.1	0.008	0.00	0.0	0.600	o	225	Pipe/Conduit		PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)	1.003	50.00	5.82	14.635	0.052	0.0	0.0	0.0	1.06	18.8	7.0	1.004	50.00	6.26	14.486	0.081	0.0	0.0	0.0	0.76	13.4	11.0	3.000	50.00	5.26	14.189	0.020	0.0	0.0	0.0	1.00	7.9	2.7	3.001	50.00	5.47	13.927	0.027	0.0	0.0	0.0	0.76	5.9	3.7	4.000	50.00	5.10	14.525	0.014	0.0	0.0	0.0	1.94	15.2	1.9	3.002	50.00	5.91	13.783	0.056	0.0	0.0	0.0	0.98	17.3	7.6	3.003	50.00	5.93	13.540	0.068	0.0	0.0	0.0	1.88	33.3	9.2	1.005	50.00	6.33	13.378	0.157	0.0	0.0	0.0	0.98	39.1	21.3	Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000	Areal Reduction Factor	1.000	MADD Factor * 10m³/ha Storage	2.000	Hot Start (mins)	0	Inlet Coefficient	0.800	Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000	Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60	Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1	Number of Input Hydrographs	0	Number of Storage Structures	0	Number of Online Controls	0	Number of Time/Area Diagrams	0	Number of Offline Controls	0	Number of Real Time Controls	0	Rainfall Model	FSR	Region	England and Wales	Return Period (years)	2	M5-60 (mm)	19.500
PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	HYD SECT	DIA (mm)	Section Type	Auto Design																																																																																																																																																																																																																																																												
1.003	13.287	0.149	89.2	0.005	0.00	0.0	0.600	o	150	Pipe/Conduit																																																																																																																																																																																																																																																													
1.004	20.099	0.115	174.8	0.029	0.00	0.0	0.600	o	150	Pipe/Conduit																																																																																																																																																																																																																																																													
3.000	15.482	0.262	59.0	0.020	5.00	0.0	0.600	o	100	Pipe/Conduit																																																																																																																																																																																																																																																													
3.001	9.676	0.094	103.4	0.007	0.00	0.0	0.600	o	100	Pipe/Conduit																																																																																																																																																																																																																																																													
4.000	11.118	0.692	16.1	0.014	5.00	0.0	0.600	o	100	Pipe/Conduit																																																																																																																																																																																																																																																													
3.002	25.581	0.243	105.3	0.015	0.00	0.0	0.600	o	150	Pipe/Conduit																																																																																																																																																																																																																																																													
3.003	2.503	0.087	28.8	0.012	0.00	0.0	0.600	o	150	Pipe/Conduit																																																																																																																																																																																																																																																													
1.005	4.226	0.024	176.1	0.008	0.00	0.0	0.600	o	225	Pipe/Conduit																																																																																																																																																																																																																																																													
PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)																																																																																																																																																																																																																																																													
1.003	50.00	5.82	14.635	0.052	0.0	0.0	0.0	1.06	18.8	7.0																																																																																																																																																																																																																																																													
1.004	50.00	6.26	14.486	0.081	0.0	0.0	0.0	0.76	13.4	11.0																																																																																																																																																																																																																																																													
3.000	50.00	5.26	14.189	0.020	0.0	0.0	0.0	1.00	7.9	2.7																																																																																																																																																																																																																																																													
3.001	50.00	5.47	13.927	0.027	0.0	0.0	0.0	0.76	5.9	3.7																																																																																																																																																																																																																																																													
4.000	50.00	5.10	14.525	0.014	0.0	0.0	0.0	1.94	15.2	1.9																																																																																																																																																																																																																																																													
3.002	50.00	5.91	13.783	0.056	0.0	0.0	0.0	0.98	17.3	7.6																																																																																																																																																																																																																																																													
3.003	50.00	5.93	13.540	0.068	0.0	0.0	0.0	1.88	33.3	9.2																																																																																																																																																																																																																																																													
1.005	50.00	6.33	13.378	0.157	0.0	0.0	0.0	0.98	39.1	21.3																																																																																																																																																																																																																																																													
Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000																																																																																																																																																																																																																																																																				
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha Storage	2.000																																																																																																																																																																																																																																																																				
Hot Start (mins)	0	Inlet Coefficient	0.800																																																																																																																																																																																																																																																																				
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000																																																																																																																																																																																																																																																																				
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60																																																																																																																																																																																																																																																																				
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1																																																																																																																																																																																																																																																																				
Number of Input Hydrographs	0	Number of Storage Structures	0																																																																																																																																																																																																																																																																				
Number of Online Controls	0	Number of Time/Area Diagrams	0																																																																																																																																																																																																																																																																				
Number of Offline Controls	0	Number of Real Time Controls	0																																																																																																																																																																																																																																																																				
Rainfall Model	FSR	Region	England and Wales																																																																																																																																																																																																																																																																				
Return Period (years)	2	M5-60 (mm)	19.500																																																																																																																																																																																																																																																																				
©1982-2020 Innovyze																																																																																																																																																																																																																																																																							

The Civil Engineering Practice		Page 3
11 Tungsten Building George Street Fishersgate BN41 1RA	Manor Nursery Angmering West Sussex	
Date 28/06/2019 File Planning Network File.MDX	Designed by S Burgess Checked by SRD	
Innovyze Network 2020.1		
<u>Synthetic Rainfall Details</u> Ratio R 0.350 Cv (Winter) 0.840 Profile Type Summer Storm Duration (mins) 30 Cv (Summer) 0.750		
©1982-2020 Innovyze		

The Civil Engineering Practice								Page 4
11 Tungsten Building George Street Fishersgate BN41 1RA				Manor Nursery Angmering West Sussex				
Date 28/06/2019				Designed by S Burgess				
File Planning Network File.MDX				Checked by SRD				
Innovyze				Network 2020.1				
<u>Summary of Critical Results by Maximum Level (Rank 1) for NETWORK 1.SWS</u>								
<u>Simulation Criteria</u>								
Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000								
Hot Start (mins) 0 MADD Factor * 10m³/ha Storage 2.000								
Hot Start Level (mm) 0 Inlet Coeffiecient 0.800								
Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000								
Foul Sewage per hectare (l/s) 0.000								
Number of Input Hydrographs 0 Number of Storage Structures 0								
Number of Online Controls 0 Number of Time/Area Diagrams 0								
Number of Offline Controls 0 Number of Real Time Controls 0								
<u>Synthetic Rainfall Details</u>								
Rainfall Model FSR Ratio R 0.350								
Region England and Wales Cv (Summer) 0.750								
M5-60 (mm) 19.500 Cv (Winter) 0.840								
Margin for Flood Risk Warning (mm) 300.0 DVD Status OFF								
Analysis Timestep Fine Inertia Status OFF								
DTS Status ON								
Profile(s) Summer and Winter								
Duration(s) (mins) 15, 30, 60, 120, 240, 360, 480, 960, 1440								
Return Period(s) (years) 100								
Climate Change (%) 40								
</								

The Civil Engineering Practice								Page 5	
11 Tungsten Building George Street Fishersgate BN41 1RA				Manor Nursery Angmering West Sussex					
Date 28/06/2019 File Planning Network File.MDX				Designed by S Burgess Checked by SRD					
Innovyze				Network 2020.1					
<u>Summary of Critical Results by Maximum Level (Rank 1) for NETWORK 1.SWS</u>									
PN	US/MH Name	Surcharged Flooded		Flow / Cap.	Overflow (l/s)	Half Drain Time (mins)	Pipe Flow (l/s)	Status	Level Exceeded
		Depth (m)	Volume (m³)						
2.000	104	0.379	0.000	0.61			7.2	SURCHARGED	
1.003	105	0.609	0.000	1.19			20.5	SURCHARGED	
1.004	106	0.600	0.000	2.48			31.2	SURCHARGED	
3.000	107	0.706	0.000	1.03			7.7	SURCHARGED	
3.001	108	0.687	0.000	2.02			11.1	SURCHARGED	
4.000	109	-0.029	0.000	0.56			8.0	OK	
3.002	110	0.497	0.000	1.37			22.5	SURCHARGED	
3.003	111	0.284	0.000	1.50			27.8	SURCHARGED	
1.005	112	0.167	0.000	2.29			62.5	SURCHARGED	
©1982-2020 Innovyze									