

TABLE 2 CHAMBER SECTION DIAMETERS

TYPICAL MANHOLE DETAIL - TYPE 1
DEPTH FROM COVER LEVEL TO SOFFIT OF PIPE 3m TO 6m

*WHEN THIS STANDARD IS SUPERSEDED BY EN 12620, THE AGGREGATES SHALL FOLLOW THE RECOMMENDATIONS IN THE UK NATIONAL GUIDANCE TO EN 12620.

Q. ALL THE ABOVE REQUIREMENTS SHALL APPLY UNLESS OTHERWISE STATED IN THE DRAINAGE LAYOUT DRAWING, MANHOLE SCHEDULE OR SPECIFICATION. IN THE EVENT OF A CONTRADICTION THE CONTRACT SPECIFIC DOCUMENTS SHALL BE DEEMED TO PREVAIL.

DRAWING STATUS:

Mountbatten House, Basing View, Basingstoke, RG21 4HJ, UK
T+ 44 (0) 1256 318 800, F+ 44 (0) 1256 318 700
wsp.com

CLIENT:

BELLWAY HOMES LTD

ARCHITECT

OSP ARCHITECTURE

SITE/PROJECT:

NEW BARN LANE, NORTH BERSTED

TITLE:

DRAINAGE STANDARD DETAILS
SHEET 1 OF 3

DRAWING No:	REV:
1643-WSP-XXX-NBL-DR-C-0508	P01

© WSP UK Ltd