

Schedule						
Symbol	Label	Quantity	Catalog Number	Description	Lumens Per Lamp	Wattage
	A	4	DSK1.2.LA084.FW	D-Series 1 Luminaire Single head column mount at 6m	8223	68
	B	8	DSK1.2.LA084.FW	D-Series 1 Luminaire Wall mount at 6m	8223	68
	C	8	DEW.LA014.NE.CGL	Denver Elite Wall Mount at 3m with 3hr Emergency battery pack	1226	12

Statistics				
Description	Symbol	Avg	Min	Max/Avg
Parking & Roadway	+	17 lux	11 lux	8.65
Unit 10	+	23 lux	14 lux	9.57
Unit 15	+	27 lux	13 lux	9.48
Unit 16	+	23 lux	17 lux	9.48
Unit 35	+	23 lux	11 lux	9.48
Walkway behind units	+	19 lux	9 lux	9.47



Plan View
Scale - 1 : 750

Note
Holograph Europe Ltd offer a Lighting Design Service in good faith and without charge, every effort is made to ensure we interpret the design specification accurately. All luminance values shown are the result of theoretical computer calculations; summated by luminaires positioned in a fixed relationship to each other and the statistical zone. In practice the values may vary due to tolerances in column installation, luminaire orientation, surface reflectance and fluctuations in power supply (voltage). Results provided within this design are derived from product specific photometry, the substitution of alternative luminaires will not produce comparable results.