

VELUX conservation roof windows

For traditional buildings



When planning dictates that a window of traditional external appearance is required, conservation roof windows should be considered. All of our conservation roof windows have the same technical features of a VELUX roof window but in a traditional black conservation style.

- Available in either centre-pivot or top-hung.
- Black external profiles and glazing bar, in RAL colour 9005.
- Recessed installation for slate and tiled roofs.
- Top-hung roof windows listed below are suitable for emergency escape.
- Other sizes and glazing options available - contact us for further information.



Conservation packages include:

- roof windows with laminated glazing as standard for safety
- recessed fixings available for a more streamlined external appearance
- insulation collar and underfelt collar provided for a weather-tight and energy efficient installation.

Conservation roof windows

External frame size (overall w x h) cm

Code	Description	CK04	CK06	FR06	MK06	MK08	UK04
Standard roof window options							
GSL SD5N2 U-value: 1.3 W/m²K	GSL SD5 roof window - 600mm recessed flanking for side up to 10mm (from 20° roof pitch)	E468	E486	E538	E566	E610	E710
GSL SD5P2 U-value: 1.3 W/m²K	GSL SD5 roof window - 600mm flanking for side up to 10mm (from 20° roof pitch)	E428	E446	E498	E539	E561	E655
GSL SD5W2 U-value: 1.3 W/m²K	GSL SD5 roof window - 600mm flanking for side up to 10mm (from 20° roof pitch)	E428	E446	E498	E539	E561	E655
GSL SD5J2 U-value: 1.3 W/m²K	GSL SD5 roof window - 600mm recessed flanking for side up to 10mm (from 20° roof pitch)	E468	E486	E538	E566	E610	E710
Emergency escape roof window options							
GPL SD5N2 U-value: 1.3 W/m²K	GPL SD5 roof window - 600mm recessed flanking for side up to 10mm (from 20° roof pitch)	-	-	-	-	E710	-
GPL SD5P2 U-value: 1.3 W/m²K	GPL SD5 roof window - 600mm flanking for side up to 10mm (from 20° roof pitch)	-	-	-	-	E691	-
GPL SD5W2 U-value: 1.3 W/m²K	GPL SD5 roof window - 600mm flanking for side up to 10mm (from 20° roof pitch)	-	-	-	-	E691	-
GPL SD5J2 U-value: 1.3 W/m²K	GPL SD5 roof window - 600mm recessed flanking for side up to 10mm (from 20° roof pitch)	-	-	-	-	E710	-