

Location (5) All Windows and Patio Doors VELFAC 200 Composite Wood / Aluminium System

VELFAC®

VELFAC 200

- the stylish and sophisticated window with double glazing

All units have uniform sightlines, whether fixed, opening or motorised, and recessed installation also delivers a 'floating' sash, adding to the contemporary finish.

The minimalistic design is a VELFAC characteristic.

The VELFAC 200 System consists of windows, casement doors and sliding casement doors in wood/aluminium.

Technical specifications

- Outward opening elements in wood / aluminium
- SBD accredited
- Extensive test programme
- Uw value: down to 1.36
- Glazing options: 24mm double glazing
- A comprehensive 12 year warranty



Location (6) Picture Window DWL Ultraline - Minimal Frame Picture Window

ultraline®

Ultraline 2

4200mm

3200mm

9 Sqm

600Kg

20mm all the way around

Stainless steel

Uw - 1.22 W/m2k

-

36mm

Rw.p 33 db - 42 db

9A (EN 12208 / EN 1027*)

4 (EN 12207 / EN 12211*)

B3 (EN 12210 / EN 1627*)

PAS 24 compliant (Maximum panel size 7 Sqm)

Ultraline 3 Available from May 2018

4200mm

3200mm

7 Sqm

900Kg

20mm all the way around

Stainless steel

-

Uw - 0.7 W/m2k

46mm

Rw.p 33 db - 42 db

9A (EN 12208 / EN 1027*)

4 (EN 12207 / EN 12211*)

B3 (EN 12210 / EN 1627*)

PAS 24 compliant (Maximum panel size 7 Sqm)

Technical Specification



Maximum panel width

Maximum panel height

Maximum panel size

Maximum panel weight

Sightline

Runner mechanism

Uw value for double glazed units (glass Ug = 1.1)

Uw value for triple glazed units (glass Ug = 0.5)

Glass thickness

Sound insulation

Water tightness

Air permeability

Wind loading

Security rating