

Fixing from outer frame to brickwork to be at maximum 500mm centres and at minimum 200mm from corners or transom/mullions.

Fixing screws must be installed in accordance with manufacturers instructions.

NOTE

structure, all fixings shown are advisory

all transoms & mullions must be reinforced

X - Indicates S716 Expansion coupling profile

all drawings and details are produced on information provided by Client and drawn to the best of knowledge

Windloadings & Values calculated based on information provided by client, please advise on any variations in site

The under Mentioned relates to

BS 8213-1:2004

contractor/fabricator.

1. Design for safety in use

4. Design for safety whe

above floor level

Wind direction (from

Category *

1000

Category *

New Heritage V/S Win

Max. seat weight / kg	width	height
1450	3000	1100

Using Inter-Range	4.00	34.00	14.00	34.00	14.00
	14.50	33.00	14.50	33.00	14.50
	27.00	32.00	17.00	32.00	17.00

Result				

details using typical	
-----------------------	--

Drawn by:	Id:
Can Hveit	2695

FR9 5AH
Telephone 01949
Fax 0493 76

[illegible][illegible]

details using typical	
-----------------------	--

Drawn by:	Id:
Can Hveit	2695

FR9 5AH
Telephone 01949
Fax 0493 76

[illegible]