DB32 Refuse Vehicle

Overall Length	7.900m
Overall Width	2.400m
Overall Body Height	3.183m
Min Body Ground Clearance	0.388m
Max Track Width	2.400m
Lock to lock time	6.00s
Kerb to Kerb Turning Radius	9.625m

NOTES/KEY:

Tracking and carry distances based on Manual for Streets and Part H of the Building Regulations:

- Refuse vehicle reverse distance – BS 5906: 2005 recommends a maximum reversing distance of 12m. Longer distances can be considered, but any reversing routes should be straight and free from obstacles or visual obstructions.
- Resident carry distance – residents should not be expected to carry waste more than 30m.
- Refuse collector carry distance – waste collection vehicles should be able to get within 25m of the collection point.
- Refuse Collection Point
- Refuse Storage Point

NB: Key (longer) carry and reversing distances indicated, others can be provided upon request

PRELIMINARY

REV. No.	DATE	DESCRIPTION	INITIALS
A	23.11.18	Revised to incorporate current Planning Layout.	AJW

Client: Persimmon Homes (Thames Valley)

Project: Phase 3 Littlehampton

Title: Refuse Tracking

MJA CONSULTING
CIVIL & STRUCTURAL ENGINEERS
Ipsum Court, The Quadrant,
Abingdon Science Park,
Oxon, OX14 3YS
Tel: 01235 555173
Fax: 01235 523226

Scale	Date	Drawing No.	Rev
1:250 @A0	Sept' 2018	5825:90	A

Checked: KTG Drawn: AJW

© This drawing is the copyright of Michael A Jennings Associates Limited and may not be copied, altered or reproduced in any way without their permission.

ARUN DISTRICT COUNCIL LICENSE 100018481