

NOTES

1. All dimensions are in metres unless stated otherwise.
2. Do not scale from this drawing. Only written dimensions are to be used.
3. This drawing should be read in conjunction with the Architect's and Structural Engineer's design drawings and specification.
4. 100mm & 150mm diameter pipework to be extra strength vitrified clay to BS EN 295 or BS 65 on Class S bed & surround.
5. 225mm pipe work to be extra strength vitrified clay to BSEN295 or BSEN65 or concrete class M to BSEN5911 on class s bed F surround.
6. Where cover to pipes is less than 1.2m concrete bed and surround should be used. Where pipes with flexible joints are used the concrete protection shall be interrupted across its full cross-section with a compressible filler.
7. Stoppered connection end of pipe to have suitable stopper applied and connected to wire which is to be connected to a stake marking the end of the pipe at ground level if laterals are to be buried during construction phase.
8. Refer to geotechnical report for sulphate resisting class and ACEC class.
9. All construction to be in accordance with Sewers for Adoption - 6th Edition & Interim Addendum and Southern Water specific requirements.
10. This drawing should be read in conjunction with Surface Water Sewer Longitudinal Sections (DSM/E4761/220 to 221),Foul Water Sewer Longitudinal Sections (DSM/E4761/201 to203) S104 Adoption Layout (DSM/E4761/402), S104 Construction Details (DSM/E4761/410 to 411), and Domestic Drainage Layouts (DSM/E4761/451 to 455).
11. Where manhole is located within soft landscaping or private drives B125 covers may be used.
12. Site layout based on Kenn Scaddan Associates Ltd site plan issued to RCP in DWG format on 04.02.2020.
13. Topographic Survey as per Siteline Level Survey, drawing number 657PG01 dated July 2012. Additional Topographic Survey as per ADA Solutions Ltd Topographical Survey, drawing number 0614-HP2-T1 dated June 2014. Ditch survey based on Siteline Ditch Level Survey, drawing number 657PG05 dated January 2019. Refer to these surveys for survey station coordinates and levels.
14. ANY VARIANCE OR DISCREPANCY MUST BE REPORTED BACK TO RCP ENGINEERING BEFORE WORK BEGINS.

CDM NOTES

1. EXISTING SERVICES, Depth of existing services must be determined prior to works commencing. The contractor is responsible for establishing underground services in accordance with HSE Guidance note HS (G) 47. Any services which would be within the proposed construction layers must be lowered to below the sub-base.

Rev. Date Details By ChkdAppd

Client:-

DREW SMITH LIMITED

Site:- SUMMER LANE PAGHAM
Drawing Title:- DOMESTIC DRAINAGE SCHEDULES

Date: February 2020 Scales: No to Scale at A1
Drawn: GD-I Checked: LD Approved: TRS

Drawing No. DSM/E4761/439

INITIAL TENDER ISSUE
SUBJECT TO PLANNING APPROVAL



Rogers Cory Partnership
Architectural and Civil Consultants
The Old School Old School Road
Hook Hampshire RG27 9NJ

T: 01256 769269 E: mail@rcpconsultants.co.uk W: rcpconsultants.co.uk

	COVER	I	A	4.749m
	5.538m	N	B	4.749m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.380m
	5.579m	N	B	4.380m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.75m
	5.493m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.542m
	5.524m	N	B	4.542m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.638m
	5.750m	N	B	4.638m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.522m
	5.522m	N	B	4.522m
	DIAMETER	E	C	4.472m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.282m
	5.397m	N	B	3.882m
	DIAMETER	E	C	
	450mm	R	D	
	Unknown	T	E	
	COVER	I	A	4.737m
	5.734m	N	B	4.812m
	SIZE	E	C	
	675mm x900mm	R	D	
	Type D	T	E	
	COVER	I	A	5.008m
	5.920m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.00m
	5.611m	N	B	
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	

	COVER	I	A	4.526m
	5.625m	N	B	4.526m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.718m
	5.587m	N	B	4.718m
	DIAMETER	E	C	4.768m
	450mm	R	D	4.768m
	450 Inspection	T	E	
	COVER	I	A	4.808m
	5.644m	N	B	4.858m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.14m
	6.140m	N	B	5.14m
	DIAMETER	E	C	5.140m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.285m
	6.081m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.393m
	6.034m	N	B	
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	4.696m
	5.746m	N	B	4.602m
	DIAMETER	E	C	4.602m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.737m
	5.787m	N	B	4.737m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.266m
	5.929m	N	B	4.267m
	DIAMETER	E	C	
	450mm	R	D	
	Unknown	T	E	
	COVER	I	A	4.298m
	5.732m	N	B	4.298m
	DIAMETER	E	C	
	450mm	R	D	
	Unknown	T	E	

	COVER	I	A	4.448m
	5.774m	N	B	4.448m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.48m
	5.654m	N	B	4.481m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.572m
	5.653m	N	B	4.521m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.75m
	5.489m	N	B	4.75m
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	3.79m
	5.464m	N	B	3.79m
	DIAMETER	E	C	3.795m
	450mm	R	D	
	Unknown	T	E	
	COVER	I	A	3.910m
	5.484m	N	B	3.86m
	DIAMETER	E	C	
	450mm	R	D	
	Unknown	T	E	
	COVER	I	A	4.117m
	5.571m	N	B	4.117m
	DIAMETER	E	C	4.117m
	450mm	R	D	
	Unknown	T	E	
	COVER	I	A	4.33m
	5.455m	N	B	4.335m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.417m
	5.459m	N	B	4.417m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.65m
	5.388m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	

	COVER	I	A	4.40m
	5.45m	N	B	4.40m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.601m
	5.651m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.180m
	5.230m	N	B	
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.453m
	5.496m	N	B	4.453m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	3.69m
	5.301m	N	B	3.69m
	DIAMETER	E	C	3.69m
	450mm	R	D	3.69m
	Unknown	T	E	
	COVER	I	A	4.440m
	5.490m	N	B	4.440m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.70m
	5.415m	N	B	
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	4.65m
	5.166m	N	B	
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	4.465m
	5.515m	N	B	4.465m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.70m
	5.342m	N	B	
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	