

	COVER	I	A	4.80m
	5.385m	N	B	4.80m
	DIAMETER	E	C	
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	4.85m
	5.411m	N	B	4.85m
	DIAMETER	E	C	4.85m
	450mm	R	D	4.85m
	450 Inspection	T	E	
	COVER	I	A	4.80m
	5.351m	N	B	4.80m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.05m
	5.542m	N	B	5.05m
	DIAMETER	E	C	5.05m
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	5.15m
	5.604m	N	B	5.15m
	DIAMETER	E	C	5.15m
	250mm	R	D	5.15m
	250 Inspection	T	E	
	COVER	I	A	4.797m
	5.797m	N	B	4.797m
	DIAMETER	E	C	4.797m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.05m
	5.729m	N	B	5.05m
	DIAMETER	E	C	5.05m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.05m
	5.784m	N	B	5.05m
	DIAMETER	E	C	5.05m
	450mm	R	D	
	450 Inspection	T	E	

	COVER	I	A	5.15m
	5.794m	N	B	5.15m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.15m
	5.797m	N	B	5.15m
	DIAMETER	E	C	5.15m
	450mm	R	D	5.15m
	450 Inspection	T	E	
	COVER	I	A	4.80m
	5.575m	N	B	4.80m
	DIAMETER	E	C	4.80m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.85m
	5.545m	N	B	4.85m
	DIAMETER	E	C	4.85m
	450mm	R	D	4.85m
	450 Inspection	T	E	
	COVER	I	A	4.545m
	5.545m	N	B	4.545m
	DIAMETER	E	C	4.545m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.80m
	5.457m	N	B	4.80m
	DIAMETER	E	C	4.80m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.80m
	5.486m	N	B	4.80m
	DIAMETER	E	C	4.80m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.663m
	5.663m	N	B	4.663m
	DIAMETER	E	C	4.663m
	450mm	R	D	
	450 Inspection	T	E	

	COVER	I	A	4.80m
	5.504m	N	B	4.80m
	DIAMETER	E	C	4.80m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.80m
	5.496m	N	B	4.80m
	DIAMETER	E	C	4.80m
	250mm	R	D	4.80m
	250 Inspection	T	E	
	COVER	I	A	4.85m
	5.763m	N	B	4.85m
	DIAMETER	E	C	4.85m
	450mm	R	D	4.85m
	450 Inspection	T	E	4.85m
	COVER	I	A	4.95m
	5.754m	N	B	4.95m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.95m
	5.842m	N	B	4.95m
	DIAMETER	E	C	4.95m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.05m
	5.813m	N	B	5.05m
	DIAMETER	E	C	5.05m
	450mm	R	D	5.05m
	450 Inspection	T	E	
	COVER	I	A	5.15m
	5.944m	N	B	5.15m
	DIAMETER	E	C	5.15m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	5.25m
	5.923m	N	B	5.25m
	DIAMETER	E	C	5.25m
	250mm	R	D	
	250 Inspection	T	E	

	COVER	I	A	5.10m
	5.999m	N	B	5.10m
	DIAMETER	E	C	5.10m
	450mm	R	D	5.10m
	450 Inspection	T	E	
	COVER	I	A	5.20m
	5.934m	N	B	5.20m
	DIAMETER	E	C	5.20m
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.187m
	5.423m	N	B	4.187m
	DIAMETER	E	C	
	450mm	R	D	
	450 Inspection	T	E	
	COVER	I	A	4.464m
	5.415m	N	B	4.464m
	DIAMETER	E	C	4.464m
	450mm	R	D	4.464m
	450 Inspection	T	E	4.464m
	COVER	I	A	5.00m
	5.752m	N	B	5.00m
	DIAMETER	E	C	5.00m
	450mm	R	D	5.00m
	450 Inspection	T	E	5.00m
	COVER	I	A	4.70m
	5.515m	N	B	4.70m
	DIAMETER	E	C	4.70m
	250mm	R	D	
	250 Inspection	T	E	
	COVER	I	A	4.696m
	5.487m	N	B	4.696m
	DIAMETER	E	C	4.696m
	250mm	R	D	4.696m
	250 Inspection	T	E	
	COVER	I	A	4.85m
	5.489m	N	B	4.85m
	DIAMETER	E	C	4.85m
	450mm	R	D	
	450 Inspection	T	E	

NOTES

- All dimensions are in metres unless stated otherwise.
- Do not scale from this drawing. Only written dimensions are to be used.
- This drawing should be read in conjunction with the Architect's and Structural Engineer's design drawings and specification.
- 100mm & 150mm diameter pipework to be extra strength vitrified clay to BS EN 295 or BS 65 on Class S bed & surround.
- 225mm pipe work to be extra strength vitrified clay to BSEN295 or BSEN65 or concrete class M to BSEN5911 on class s bed F surround.
- Where cover to pipes is less than 1.2m concrete bed and surround should be used. Where pipes with flexible joints are used the concrete protection shall be interrupted across its full cross-section with a compressible filler.
- Stoppered connection end of pipe to have suitable stopper applied and connected to wire which is to be connected to a stake marking the end of the pipe at ground level if laterals are to be buried during construction phase.
- Refer to geotechnical report for sulphate resisting class and ACEC class.
- All construction to be in accordance with Sewers for Adoption - 6th Edition & Interim Addendum and Southern Water specific requirements.**
- This drawing should be read in conjunction with Surface Water Sewer Longitudinal Sections (DSM/E4761/220 to 221), Foul Water Sewer Longitudinal Sections (DSM/E4761/201 to 203) S104 Adoption Layout (DSM/E4761/402), S104 Construction Details (DSM/E4761/410 to 411), and Domestic Drainage Layouts (DSM/E4761/451 to 455).
- Where manhole is located within soft landscaping or private drives B125 covers may be used.
- Site layout based on Kenn Scaddan Associates Ltd site plan issued to RCP in DWG format on 04.02.2020.
- Topographic Survey as per Siltline Level Survey, drawing number 657PG01 dated July 2012. Additional Topographic Survey as per ADA Solutions Ltd Topographical Survey, drawing number 0614-HP2-T1 dated June 2014. Ditch survey based on Siltline Ditch Level Survey, drawing number 657PG05 dated January 2019. Refer to these surveys for survey station coordinates and levels.
- ANY VARIANCE OR DISCREPANCY MUST BE REPORTED BACK TO RCP ENGINEERING BEFORE WORK BEGINS.**

CDM NOTES

- EXISTING SERVICES. Depth of existing services must be determined prior to works commencing. The contractor is responsible for establishing underground services in accordance with HSE Guidance note HS (G) 47. Any services which would be within the proposed construction layers must be lowered to below the sub-base.

Rev./ Date Details By Chkd/ Appd

Client:-

DREW SMITH LIMITED

Site:-

SUMMER LANE
PAGHAM

Drawing Title:-

DOMESTIC
DRAINAGE
SCHEDULES

Date: February 2020

Scales: No to Scale at A1

Drawn: GD-I

Checked: LD

Approved: TRS

Drawing No.

DSM/E4761/446

INITIAL TENDER ISSUE

SUBJECT TO PLANNING APPROVAL



Rogers Cory Partnership
Architectural and Civil Consultants
The Old School Old School Road
Hook Hampshire RG27 9NJ

T: 01256 769269 E: mail@rcpconsultants.co.uk W: rcpconsultants.co.uk