

RADIO PLANNING AND PROPAGATION

An introduction to how radio networks are planned and the limitations associated with the technology.

When planning cellular telecommunications networks engineers use specialist software to predict, with a high degree of confidence, the behaviour of cellular transmissions. This then enables the operator to calculate how many cell sites are needed to provide the level of coverage and capacity required by their customers.

The strength of radio signals detected at a receiving device naturally reduces the further away it is from the transmitter. In general the reduction (or decay) in signal power is affected by a number of variables. The main factors are:

- signal frequency,
- distance (from the transmitter),
- terrain (such as hills),
- clutter (such as buildings, foliage, vehicles, and water) and
- atmospheric conditions (such as rain).

A reduction in the strength of the radio signal increases the likelihood of dropped calls and reduced data rates for internet browsing, for example.

Clutter

Any physical object obstructing the propagation of radio signals causes a reduction in signal strength reaching a customer's device. A common term for these objects is 'clutter'. The more obvious examples are buildings and geographical terrain such as hills and trees.

Buildings cause a varying amount of signal reduction depending on their height, construction, thickness of walls, amount of windows etc. Glass causes a lower reduction in signal than brick/concrete walls.

Customers will inadvertently be aware of this by finding that sometimes they need to go near windows, a higher floor of a building or even outside in order to achieve a stronger signal for their mobile devices.

Tree Clutter

The effects of trees on signal degradation can be significant. Signal absorption and shadowing effects vary according to vegetation and density, and are caused by the main tree trunk, branches and leaves.

Cell sites located in or near trees will have signals significantly reduced. As a result a number of extra sites may need to be built locally in order to counter-effect this.

Signal variation throughout the seasons is also a practical concern. Leaves on trees in the spring and summer can cause shadowing and reduce radio voice quality and increase the number of dropped calls.

As a result the bottom of an antenna should a) be above the top level of the trees, b) allow greater height due to the antenna downtilt at build or for future requirements and c) allow some room for future growth of the trees.

CTIL Radio Planning and Propagation v.2
2016 CTIL

The 'Dual Stack' is by far the preferred option. This is due to a number of factors including greater flexibility & control for different technologies and providing optimum service performance to customers.

Site upgrades such as network consolidation between Vodafone and Telefonica and/ or new 4G technologies facilitate a Single Stack structure being upgraded to a Dual Stack structure. In a straight swap scenario at equal height the new lower aperture antennas would be lower than they were originally - resulting in significantly reduced coverage. To ensure existing coverage is maintained the whole structure needs to be increased in height.

Clutter changes

A more extreme example is when the local clutter or tree lines have changed, or are such that the mobile signals are blocked, resulting in lower quality calls and downloads for mobile device users. To provide sufficient services to customers height increases on existing masts or additional new masts are required. The former is the preferred option in many cases.

ICNIRP Compliance

The addition of new technologies and mast sharing affects ICNIRP compliance – a higher minimum mast height is required in some cases.