



LUMINAIRE SCHEDULE						
Symbol	Label	Qty	Catalog Number	Description	Lamp	Watts
	A1	1	1 x DSX1 2 LA064 AY on 6m Column	D-Series 1 Luminaire	LED C.6000LM-4000K	52
	A1st	1	1 x DSX1 2 LA064 AY BLS on 6m Column and Backlight Shield .5 Degree Tilt Bracket	D-Series 1 Luminaire with Back light shield	LED C.6000LM-4000K	52
	B11	3	1 x DSX1 2 LA064 FW on 6m Column .5 Degree Tilt Bracket	D-Series 1 Luminaire	LED C.6000LM-4000K	52
	B1st	1	DSX1 2 LA064 FW BLS on 6m Column and Backlight Shield .5 Degree Tilt Bracket	D-Series 1 Luminaire with Back light shield	LED C.6000LM-4000K	52
	C	18	AME RO at 3m AFPL	Amenity Round 15605		20

STATISTICS					
Description	Symbol	Avg	Max	Min	Min/Avg
Access	+	8 lux	15 lux	2 lux	0.25
Access Road Link	+	10 lux	20 lux	4 lux	0.40
Parking	+	10 lux	28 lux	3 lux	0.30
SPILL	+	0 lux	18 lux	0 lux	N/A

NOTES
PRELIMINARY NOTIONAL DESIGN ONLY.
DETAILED EXTERNAL LIGHTING AND
EMERGENCY LIGHTING DESIGN SHALL BE
SUBJECT TO A SITE SURVEY AND LIAISON
WITH THE CLIENT.

