


Lake Lane, Barnham, Bognor Regis PO22 0AJ

04 October 2024

### SuDS Drainage Technical Note

1. GTA Civils and Transport Ltd. was commissioned to prepare a SuDS Technical Note. This should be read in conjunction with the Stage 2 FRA report, prepared by GTA C&T, 3<sup>rd</sup> Issue dated 19 April 2024.
2. This Technical Note provides responses to the Lead Local Flood Authority's (LLFA) list of comments (objections) contained in the memorandum dated 01 May 2024.
3. The outstanding items were discussed during an online meeting conducted between the Client, architect and Paul Cann, the LLFA engineer - on 12 August 2024.
4. The items that were discussed were as follows:
  1. Paul Cann mentioned at the outset that he is familiar with this site – having walked over it about 9-10 years ago. There is a spring close to the NW corner that was buried by the previous owner. This is denoted on the topographic survey as a man-made ditch spur running south – north – shown in Figure 1 below.
  2. The layout should be amended such that any flows from this area are able to flow without risk of flooding the units.
  3. Condition of the culverted watercourse to the NW, immediately downstream of the site – specifically; this flows through Kilkenny's demise.
  4. Attenuation tank: the LLFA want to ensure that the effects of buoyancy have been accounted for in the design.



**Figure 1: Man-made Ditch Spur Conveying Spring Water to the Established Watercourse**

5. Spring and man-made ditch spur. The Applicant has confirmed that this area is no more than a localised depression – not a fully formed ditch as such.
6. GTA stated that they would action a CCTV survey as soon as possible. This was done on 03/09 by Eyes on Drainage – refer to the report in Appendix A.
7. The owner of Kilkenny did not allow the surveyor to enter his property, meaning that the condition of the culvert pipe is still unknown. The LLFA acknowledges that the culvert is free-flowing and that the owner (Kilkenny) has a maintenance regime. The post-development runoff rate will be restricted to Qbar, meaning that the runoff rate will be reduced in all storm scenarios greater than the mean (approximately 1 in 2 years).
8. The drainage and levels strategies have been amended to satisfy the LLFA's stated need for lowering the site's levels and to confirm as much of the downstream watercourse's condition as possible. CV values have been increased to 1; the drainage has been designed with level soffits, not invert; the 33.3% (1 in 30 years) calculation has added – refer to Appendix C. 10% allowance for Urban Creep has been added to the drainage calculations – refer to the catchment areas layout (in Appendix B) and calculations in Appendix C.
9. Land drains have been added – to convey any underground spring water to the NW corner between Plots 6 and 7.
10. The attenuation tank's invert level is set at 8.20m AOD. The existing ground level in this area is 8.76m - 9.04m AOD, so the tank's invert is only 560mm below the lowest local level. The proposed ground levels are now raised slightly higher at 9.3m, thereby providing additional cover. Buoyancy calculations are shown in Appendix D: these prove that both the tank and pond will work with an anticipated groundwater table level at the lowest point on the site.

**Conclusion:**

It is contended that all the LLFA's outstanding items of contention have been addressed – in full. Although the condition of the culvert has not been confirmed by CCTV survey, this is not in question – as the LLFA have stated that its owner has been maintaining it satisfactorily.

- End of Technical Note -

## Appendix A

### CCTV Drainage Survey Report

**Project**


**Project Name:** Park Rd Culvert - Barnham

**Project Description:** Culvert Survey

**Project Status:** Complete

**Project Date:** 18/08/2024

**Inspection Standard:** MSCC5 Sewers & Drainage GB (SRM5 Scoring)



**EYES ON DRAINAGE**

**CCTV-Trace-Plot-Map-Repair**

## Table of Contents


Project Name	Project Number	Project Date
Park Rd Culvert - Barnham		18/08/2024
Project Information .....		P-1
Scoring Summary .....		P-3
Section Profile .....		P-4
Section Summary .....		P-5
Section Item 1: HW1 > HW2 (HW1X) .....		1
Disclaimer .....		3

## Project Information

Project Name	Project Number	Project Date
Park Rd Culvert - Barnham		18/08/2024

### Client

**Company:** Folkes Architects  
**Department:** The Old Forge  
**Street:** 6 Church St  
**Town or City:** Storrington  
**County:** West sussex  
**Post Code:** RH20 4LA




### Site

**Description:** North of Lake Lane  
**Department:** Kilkenny  
**Street:** Park Rd  
**Town or City:** Barnham  
**County:** West Sussex  
**Post Code:** PO22 0AJ

### Contractor

**Company:** Eyes On Drainage Services Ltd  
**Contact:** Jay Young  
**Department:** Merrion House  
**Street:** Bines Green  
**Town or City:** Horsham  
**County:** West Sussex  
**Post Code:** RH13 8EH  
**Phone:** 01403 710971  
**Mobile:** 077111 84951  
**Email:** info@eyesondrainage.co.uk



## Project Information

Project Name  
Park Rd Culvert - Barnham

Project Number

Project Date  
18/08/2024

### Project Drawing, Page 'Park Rd Culvert - Barnham'



## Scoring Summary

Project Name Park Rd Culvert - Barnham	Project Number	Project Date 18/08/2024
---	----------------	----------------------------

### Structural Defects

Section	PLR	Grade	Description
All inspected pipes are in an acceptable structural condition (< grade 3).			

### Service / Operational Condition

Section	PLR	Grade	Description
All inspected pipes are in an acceptable service condition (< grade 3).			

### Abandoned Surveys

Section	PLR	Description
All inspections complete, none are abandoned.		

### Information

These scoring summaries are based on the SRM grading from the WRc.

## Section Profile

**Project Name**  
 Park Rd Culvert - Barnham

**Project Number**

**Project Date**  
 18/08/2024

### Circular, 450 mm

Item No.	Upstream Node	Downstream Node	Date	Road	Material	Total Length	Inspected Length
1	HW1	HW2	18/08/2024	Park Rd	Concrete	55.00 m	55.00 m

**Total: 1 Inspection x Circular 450 mm, 0 mm = 55.00 m Total Length and 55.00 m Inspected Length**

Total: 1 Inspection = 55.00 m Total Length and 55.00 m Inspected Length

## Section Summary

Project Name	Project Number	Project Date
Park Rd Culvert - Barnham		18/08/2024

Number of sections	1
Total length of sections	55.00 m
Total length of inspected sections	55.00 m
Total length of not inspected sections	0.00 m
Number of abandoned inspections	0
Number of section inspection photos	4
Number of section inspection videos	0
Number of section inspection scans	0
Number of section inclination measurements	0

<b>PLR:</b>	HW1X	<b>Upstream Node:</b>	HW1
<b>Inspection Direction:</b>	Downstream	<b>Downstream Node:</b>	HW2
<b>Inspected Length:</b>	55.00 m	<b>Dia/Height:</b>	450 mm
<b>Total Length:</b>	55.00 m	<b>Material:</b>	Concrete

No.	m+	Code	Observation
1	0.00	OF	Start node, outfall, reference: HW1, Located within private grounds
2	0.00	WL	Water level, 0% of the vertical dimension
3	0.00	WL	Water level, 70% of the vertical dimension
4	55.00	OFF	Finish node, outfall, reference: HW2, Unable to carry out full CCTV survey due to permissions.

**Section Inspection - 18/08/2024 - HW1X**


Item No.	Insp. No.	Date	Time	Client's Job Ref	Weather	Pre Cleaned	PLR
1	1	18/08/24	7:51	Not Specified	No Rain Or Snow	No	HW1X
<b>Operator</b> JY		<b>Vehicle</b> BV21 CDX		<b>Camera</b> Not Specified	<b>Preset Length</b> Not Specified	<b>Legal Status</b> Watercourse	<b>Alternative ID</b> Not Specified

<b>Town or Village:</b>	Barnham	<b>Inspection Direction:</b>	Downstream	<b>Upstream Node:</b>	HW1
<b>Road:</b>	Park Rd	<b>Inspected Length:</b>	55.00 m	<b>Upstream Pipe Depth:</b>	
<b>Location:</b>	Gardens (private)	<b>Total Length:</b>	55.00 m	<b>Downstream Node:</b>	HW2
<b>Surface Type:</b>	Various	<b>Joint Length:</b>		<b>Downstream Pipe Depth:</b>	

<b>Use:</b>	Culverted watercourse	<b>Pipe Shape:</b>	Circular
<b>Type of Pipe:</b>	Gravity drain/sewer	<b>Dia/Height:</b>	450 mm
<b>Flow Control:</b>	No flow control	<b>Material:</b>	Concrete
<b>Year Constructed:</b>	Not Specified	<b>Lining Type:</b>	No Lining
<b>Inspection Purpose:</b>	Routine inspection	<b>Lining Material:</b>	No Lining

**Comments:**
**Recommendations:**

Scale: 1:477	Position [m]	Code	Observation	MPEG	Photo	Grade
--------------	--------------	------	-------------	------	-------	-------

**Depth: m**
**HW1**


0.00 OF Start node, outfall, reference: HW1: Located within private grounds

1, 2

0.00 WL Water level, 0% of the vertical dimension

0.00 WL Water level, 70% of the vertical dimension

00:00:01

55.00 OFF Finish node, outfall, reference: HW2: Unable to carry out full CCTV survey due to permissions.

3, 4

**HW2**
**Depth: m**

Construction Features					Miscellaneous Features						
Structural Defects					Service & Operational Observations						
STR No.	Def	STR Peak	STR Mean	STR Total	STR Grade	SER No.	Def	SER Peak	SER Mean	SER Total	SER Grade
0		0.0	0.0	0.0	1.0	0		0.0	0.0	0.0	1.0

**Section Pictures - 18/08/2024 - HW1X**

Item No.	Inspection Direction	PLR	Client's Job Ref	Contractor's Job Ref
1	Downstream	HW1X		


**1, 0.00 m**

Start node, outfall, reference: HW1, Located within private grounds


**2, 0.00 m**

Start node, outfall, reference: HW1, Located within private grounds


**3, 55.00 m**

Finish node, outfall, reference: HW2, Unable to carry out full CCTV survey due to permissions.


**4, 55.00 m**

Finish node, outfall, reference: HW2, Unable to carry out full CCTV survey due to permissions.

## **Disclaimer**

Although every effort has been made to produce a thorough and precise report, Eyes On Drainage Services Ltd cannot be held liable for any discrepancies or omissions.

Furthermore Eyes On Drainage Services Ltd cannot be held responsible for any actions taken based on the information supplied within this report.

## Appendix B

### Drainage Strategy and Catchment Areas Layouts





## Appendix C

### Drainage Calculations & Anti-Buoyancy Calculation

Design Settings

Rainfall Methodology	FEH-22	Maximum Time of Concentration (mins)	0.00	Preferred Cover Depth (m)	1.200
Return Period (years)	100	Maximum Rainfall (mm/hr)	0.0	Include Intermediate Ground	x
Additional Flow (%)	0	Minimum Velocity (m/s)	1.00	Enforce best practice design rules	x
CV	0.750	Connection Type	Level Soffits		
Time of Entry (mins)	5.00	Minimum Backdrop Height (m)	1.000		

Adoptable Manhole Type

Max Width (mm)	Diameter (mm)						
374	1200	499	1350	749	1500	900	1800

&gt;900 Link+900 mm

Max Depth (m)	Diameter (mm)	Max Depth (m)	Diameter (mm)
1.500	1050	99.999	1200

Circular Link Type

Shape	Circular	Barrels	1	Auto Increment (mm)	75	Follow Ground	x
-------	----------	---------	---	---------------------	----	---------------	---

Available Diameters (mm)

100 150

Nodes

Name	Area (ha)	T of E (mins)	Cover Level (m)	Diameter (mm)	Easting (m)	Northing (m)	Depth (m)
PS1	0.014	5.00	10.168	600	496889.952	104683.005	1.008
PS2	0.013	5.00	10.268	450	496898.756	104711.816	1.535
PS3	0.012	5.00	9.978	450	496906.735	104740.574	1.444
PS4	0.035	5.00	9.633	450	496914.791	104760.740	1.318
PS5	0.010	5.00	9.450	450	496925.103	104766.769	1.206
PS6			8.814	600	496937.311	104780.896	0.679
Headwall 2	0.009	5.00	8.700	450	496938.131	104783.756	0.583

Nodes

Name	Area (ha)	T of E (mins)	Cover Level (m)	Diameter (mm)	Easting (m)	Northing (m)	Depth (m)
Headwall 1			8.700	450	496943.630	104797.400	0.600
PS9	0.024	\$ 00	9.231	450	496913.996	104837.170	0.748
PS10	0.013	\$ 00	9.293	450	496941.267	104828.813	1.075
PS15	0.003	\$ 00	9.000	450	496950.440	104822.685	0.847
Headwall 4	0.010	\$ 00	8.700	450	496950.335	104820.715	0.559
Headwall 3			8.700	450	496945.502	104802.389	0.600
PS16	0.009	\$ 00	9.262	180	496918.066	104780.528	0.812
PS17	0.031	\$ 00	9.334	450	496923.887	104778.637	1.111
PS18			9.136	600	496934.438	104801.560	1.061
PS7			9.100	1200	496944.558	104799.948	1.085
Outfall			9.000	450	496947.039	104799.760	1.000

Links

Name	US Node	DS Node	Length (m)	ks (mm) / n	US IL (m)	DS IL (m)	Fall (m)	Slope (1:X)	Dia (mm)	T of C (mins)
1.000	PS1	PS2	30.126	0.600	9.160	8.783	0.377	79.9	150	0.00
1.001	PS2	PS3	29.844	0.600	8.733	8.534	0.199	160.0	150	0.00
1.002	PS3	PS4	21.716	0.600	8.534	8.390	0.144	150.8	150	0.00
1.003	PS4	PS5	11.945	0.600	8.315	8.244	0.071	168.2	225	0.00
1.004	PS5	PS6	18.671	0.600	8.244	8.135	0.109	171.3	225	0.00
1.005	PS6	Headwall 2	2.975	0.600	8.135	8.117	0.018	165.3	225	0.00

Name	Vel (m/s)	Cap (l/s)	US Depth (m)	DS Depth (m)	$\Sigma$ Area (ha)	$\Sigma$ Add Inflow (l/s)	Pro Depth (mm)	Pro Velocity (m/s)
1.000	1.125	19.9	0.858	1.335	0.014	0.0	0	0.000
1.001	0.818	14.5	1.385	1.294	0.027	0.0	0	0.000
1.002	0.816	14.4	1.294	1.003	0.039	0.0	0	0.000
1.003	1.005	40.0	1.003	0.981	0.074	0.0	0	0.000
1.004	0.996	39.6	0.981	0.484	0.084	0.0	0	0.000
1.005	1.014	40.3	0.404	0.358	0.084	0.0	0	0.000

Links

Name	US Node	DS Node	Length (m)	ks (mm) / n	US IL (m)	DS IL (m)	Fall (m)	Slope (1:X)	Dia (mm)	T of C (mins)
1.006	Headwall 2	Headwall 1	14.711	0.600	8.117	8.100	0.017	865.4	225	0.00
1.007	Headwall 1	PS7	2.711	0.600	8.100	8.015	0.083	31.9	225	0.00
2.000	PS9	PS10	28.523	0.600	8.483	8.293	0.190	150.1	150	0.00
2.001	PS10	PS15	11.031	0.600	8.218	8.153	0.068	169.7	225	0.00
2.002	PS15	Headwall 4	1.973	0.600	8.153	8.141	0.012	164.4	225	0.00
2.003	Headwall 4	Headwall 3	18.952	0.600	8.141	8.100	0.041	462.2	225	0.00
2.004	Headwall 3	PS7	2.618	0.600	8.100	8.015	0.088	30.3	225	0.00
3.000	PS16	PS17	6.120	0.600	8.450	8.298	0.152	40.3	150	0.00
3.001	PS17	PS18	25.234	0.600	8.223	8.075	0.148	170.5	225	0.00
3.002	PS18	PS7	10.248	0.600	8.075	8.015	0.060	170.3	225	0.00
1.008	PS7	Outfall	2.488	0.600	8.015	8.000	0.018	165.9	225	0.00

Name	Vel (m/s)	Cap (l/s)	US Depth (m)	DS Depth (m)	$\Sigma$ Area (ha)	$\Sigma$ Add Inflow (l/s)	Pro Depth (mm)	Pro Velocity (m/s)
1.006	0.437	17.4	0.008	0.075	0.093	0.0	0	0.000
1.007	2.324	92.4	0.375	0.800	0.093	0.0	0	0.000
2.000	0.818	14.4	0.008	0.050	0.024	0.0	0	0.000
2.001	1.001	39.8	0.850	0.621	0.037	0.0	0	0.000
2.002	1.017	40.4	0.002	0.394	0.040	0.0	0	0.000
2.003	0.602	23.9	0.004	0.375	0.050	0.0	0	0.000
2.004	2.366	94.1	0.375	0.800	0.050	0.0	0	0.000
3.000	1.590	28.1	0.002	0.806	0.009	0.0	0	0.000
3.001	0.998	39.7	0.006	0.006	0.040	0.0	0	0.000
3.002	0.997	39.7	0.006	0.000	0.040	0.0	0	0.000
1.008	1.012	40.2	0.000	0.775	0.183	0.0	0	0.000

Simulation Settings

Rainfall Methodology	FEH-22	Analysis Speed	Normal	Additional Storage (m <sup>3</sup> /ha)	0.0
Summer CV	1.000	Skip Steady State	x	Check Discharge Rate(s)	x
Winter CV	1.000	Drain Down Time (mins)	60	Check Discharge Volume	x

**Storm Durations**

15	30	60	120	180	240	360	480	600	720	960	1440	2160	2880	4320	5760	7200	8640
----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------

Return Period (years)	Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)	Return Period (years)		Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)
				2	100			
30	0	0	0					

#### Node PS7 Online Hydro-Brake® Control

Flap Valve	x	Objective	(HE) Minimise upstream storage
Replaces Downstream Link	x	Sump Available	✓
Invert Level (m)	8.015	Product Number	CTL-SHE-0048-1100-1085-1100
Design Depth (m)	1.085	Min Outlet Diameter (m)	0.075
Design Flow (l/s)	1.1	Min Node Diameter (mm)	1200

#### Node Headwall 3 Depth/Area Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Safety Factor	2.0	Invert Level (m)	8.100
Side Inf Coefficient (m/hr)	0.00000	Porosity	1.00	Time to half empty (mins)	

Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )
0.000	16.8	0.0	0.200	37.6	0.0	0.400	60.5	0.0	0.600	85.4	0.0
0.100	26.8	0.0	0.300	48.8	0.0	0.500	72.7	0.0	0.601	85.4	0.0

#### Node Headwall 1 Depth/Area Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Safety Factor	2.0	Invert Level (m)	8.100
Side Inf Coefficient (m/hr)	0.00000	Porosity	1.00	Time to half empty (mins)	

Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )	Depth (m)	Area (m <sup>2</sup> )	Inf Area (m <sup>2</sup> )
0.000	14.4	0.0	0.200	34.3	0.0	0.400	57.3	0.0	0.600	83.1	0.0
0.100	23.9	0.0	0.300	45.4	0.0	0.500	69.8	0.0	0.601	83.1	0.0

**Node PS18 Lined Soakaway Storage Structure**

Base Inf Coefficient (m/hr)	0.00000	Porosity	0.95	Ring Diameter (m)	1.000	Depth (m)	0.500
Side Inf Coefficient (m/hr)	0.00000	Invert Level (m)	8.100	Pit Width (m)	9.000	Inf Depth (m)	
Safety Factor	2.0	Time to half empty (mins)		Pit Length (m)	24.000	Number Required	1

Results for 2 year Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node	Flood Vol (m³)	Status
15 minute summer	PS1	11	9.197	0.037	2.6	0.0103	0.0000	OK
15 minute summer	PS2	11	8.793	0.060	5.0	0.0095	0.0000	OK
15 minute summer	PS3	11	8.610	0.076	7.1	0.0121	0.0000	OK
15 minute summer	PS4	11	8.411	0.096	13.3	0.0153	0.0000	OK
15 minute summer	PS5	11	8.344	0.100	15.2	0.0158	0.0000	OK
30 minute summer	PS6	19	8.264	0.129	13.7	0.0365	0.0000	OK
30 minute summer	Headwall 2	19	8.252	0.135	15.4	0.0214	0.0000	OK
360 minute winter	Headwall 1	344	8.230	0.130	6.0	2.7021	0.0000	OK
15 minute summer	PS9	11	8.541	0.058	4.5	0.0091	0.0000	OK
15 minute summer	PS10	10	8.282	0.064	6.8	0.0102	0.0000	OK
15 minute summer	PS15	11	8.244	0.091	7.3	0.0145	0.0000	OK
15 minute summer	Headwall 4	11	8.238	0.097	9.0	0.0154	0.0000	OK
360 minute winter	Headwall 3	344	8.230	0.130	6.1	3.0629	0.0000	OK
15 minute summer	PS16	10	8.476	0.026	1.7	0.0006	0.0000	OK
15 minute summer	PS17	10	8.295	0.072	7.6	0.0115	0.0000	OK

Link Event (Velocity)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute summer	PS1	1.000	PS2	2.5	0.771	0.128	0.0991	
15 minute summer	PS2	1.001	PS3	4.9	0.644	0.339	0.2323	
15 minute summer	PS3	1.002	PS4	7.0	0.800	0.488	0.1911	
15 minute summer	PS4	1.003	PS5	13.4	0.806	0.334	0.1980	
15 minute summer	PS5	1.004	PS6	15.2	0.763	0.383	0.3716	
15 minute summer	PS6	1.005	Headwall 2	15.0	0.653	0.372	0.0710	
15 minute summer	Headwall 2	1.006	Headwall 1	16.4	1.044	0.946	0.3083	
30 minute summer	Headwall 1	1.007	PS7	22.5	0.792	0.244	0.0753	
15 minute summer	PS9	2.000	PS10	4.4	0.714	0.303	0.1749	
15 minute summer	PS10	2.001	PS15	6.8	0.577	0.170	0.1334	
15 minute summer	PS15	2.002	Headwall 4	7.2	0.488	0.178	0.0310	
15 minute summer	Headwall 4	2.003	Headwall 3	8.8	0.836	0.368	0.2962	
30 minute winter	Headwall 3	2.004	PS7	18.2	0.728	0.193	0.0686	
15 minute summer	PS16	3.000	PS17	1.7	0.854	0.060	0.0120	
15 minute summer	PS17	3.001	PS18	7.5	1.072	0.189	0.1871	

Results for 2 year Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US	Peak	Level	Depth	Inflow	Node	Flood	Status
	Node	(mins)	(m)	(m)	(l/s)	Vol (m <sup>3</sup> )	(m <sup>3</sup> )	
360 minute winter	PS18	344	8.230	0.155	5.9	26.8738	0.0000	OK
360 minute winter	PS7	344	8.230	0.215	13.5	0.2434	0.0000	OK
360 minute winter	Outfall	344	8.023	0.023	0.9	0.0000	0.0000	OK

Link Event (Velocity)	US	Link	DS	Outflow	Velocity	Flow/Cap	Link	Discharge
	Node		Node	(l/s)	(m/s)		Vol (m <sup>3</sup> )	Vol (m <sup>3</sup> )
15 minute summer	PS18	3.002	PS7	-14.2	-0.643	-0.358	0.2254	
360 minute winter	PS7	1.008	Outfall	0.9	0.400	0.022	0.0055	19.5

Results for 30 year Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute summer	PS1	10	9.220	0.060	6.6	0.0170	0.0000	OK
15 minute summer	PS2	12	8.863	0.130	12.5	0.0207	0.0000	OK
15 minute summer	PS3	11	8.759	0.225	18.0	0.0357	0.0000	SURCHARGED
15 minute summer	PS4	11	8.572	0.257	32.3	0.0409	0.0000	SURCHARGED
15 minute summer	PS5	11	8.513	0.269	36.1	0.0428	0.0000	SURCHARGED
15 minute summer	PS6	12	8.414	0.279	34.2	0.0791	0.0000	SURCHARGED
30 minute summer	Headwall 2	20	8.388	0.271	35.8	0.0431	0.0000	SURCHARGED
480 minute winter	Headwall 1	472	8.387	0.287	6.5	8.2633	0.0000	SURCHARGED
15 minute summer	PS9	10	8.584	0.101	11.3	0.0161	0.0000	OK
480 minute winter	PS10	472	8.388	0.170	1.9	0.0271	0.0000	OK
480 minute winter	PS15	464	8.391	0.238	6.2	0.0379	0.0000	SURCHARGED
480 minute winter	Headwall 4	472	8.393	0.252	3.8	0.0400	0.0000	SURCHARGED
480 minute winter	Headwall 3	464	8.386	0.286	9.6	9.1038	0.0000	SURCHARGED
15 minute summer	PS16	10	8.492	0.042	4.3	0.0010	0.0000	OK
480 minute winter	PS17	472	8.387	0.164	2.1	0.0260	0.0000	OK

Link Event (Velocity)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute summer	PS1	1.000	PS2	6.5	0.994	0.326	0.2304	
15 minute summer	PS2	1.001	PS3	12.3	0.789	0.850	0.5054	
15 minute summer	PS3	1.002	PS4	16.4	0.951	1.141	0.3823	
15 minute summer	PS4	1.003	PS5	31.4	0.910	0.787	0.4751	
15 minute summer	PS5	1.004	PS6	34.2	0.891	0.863	0.7426	
15 minute summer	PS6	1.005	Headwall 2	33.7	0.848	0.837	0.1183	
15 minute summer	Headwall 2	1.006	Headwall 1	37.3	1.199	2.150	0.5800	
30 minute summer	Headwall 1	1.007	PS7	26.3	0.817	0.284	0.1078	
15 minute summer	PS9	2.000	PS10	11.0	0.891	0.763	0.3527	
15 minute summer	PS10	2.001	PS15	16.9	0.662	0.424	0.3031	
15 minute summer	PS15	2.002	Headwall 4	18.0	0.568	0.446	0.0649	
15 minute winter	Headwall 4	2.003	Headwall 3	20.6	0.927	0.862	0.6366	
60 minute winter	Headwall 3	2.004	PS7	16.3	0.689	0.173	0.1032	
15 minute summer	PS16	3.000	PS17	4.3	1.094	0.152	0.0249	
15 minute summer	PS17	3.001	PS18	18.8	1.415	0.475	0.3937	

Results for 30 year Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US	Peak	Level	Depth	Inflow	Node	Flood	Status
	Node	(mins)	(m)	(m)	(l/s)	Vol (m <sup>3</sup> )	(m <sup>3</sup> )	
480 minute winter	PS18	472	8.387	0.312	6.2	59.0041	0.0000	SURCHARGED
480 minute winter	PS7	472	8.387	0.372	9.5	0.4205	0.0000	SURCHARGED
2880 minute winter	Outfall	2340	8.023	0.023	0.9	0.0000	0.0000	OK

Link Event (Velocity)	US	Link	DS	Outflow	Velocity	Flow/Cap	Link	Discharge
	Node	Node		(l/s)	(m/s)		Vol (m <sup>3</sup> )	Vol (m <sup>3</sup> )
15 minute summer	PS18	3.002	PS7	-36.0	-1.126	-0.908	0.3564	
2880 minute winter	PS7	1.008	Outfall	0.9	0.401	0.022	0.0055	117.0

Results for 100 year +45% CC Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
15 minute summer	PS1	12	9.901	0.741	12.0	0.2096	0.0000	FLOOD RISK
15 minute summer	PS2	12	9.829	1.096	21.8	0.1742	0.0000	SURCHARGED
15 minute summer	PS3	12	9.562	1.028	23.7	0.1635	0.0000	SURCHARGED
15 minute summer	PS4	12	9.125	0.810	49.3	0.1288	0.0000	SURCHARGED
15 minute summer	PS5	12	8.989	0.745	55.7	0.1184	0.0000	SURCHARGED
15 minute summer	PS6	12	8.733	0.598	54.1	0.1692	0.0000	FLOOD RISK
720 minute winter	Headwall 2	705	8.692	0.575	5.9	0.0914	0.0000	FLOOD RISK
720 minute winter	Headwall 1	705	8.692	0.592	7.4	27.3465	0.0000	FLOOD RISK
15 minute summer	PS9	11	8.921	0.438	20.6	0.0697	0.0000	SURCHARGED
720 minute winter	PS10	720	8.693	0.475	2.5	0.0755	0.0000	SURCHARGED
720 minute winter	PS15	705	8.695	0.542	2.6	0.0862	0.0000	SURCHARGED
720 minute winter	Headwall 4	720	8.694	0.553	3.3	0.0879	0.0000	FLOOD RISK
720 minute winter	Headwall 3	705	8.692	0.592	5.8	29.1332	0.0000	FLOOD RISK
720 minute winter	PS16	705	8.692	0.242	0.6	0.0060	0.0000	SURCHARGED
720 minute winter	PS17	705	8.691	0.468	2.6	0.0744	0.0000	SURCHARGED

Link Event (Velocity)	US Node	Link	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute summer	PS1	1.000	PS2	11.1	1.019	0.556	0.5304	
15 minute summer	PS2	1.001	PS3	16.4	0.931	1.133	0.5254	
15 minute summer	PS3	1.002	PS4	24.3	1.378	1.683	0.3823	
15 minute summer	PS4	1.003	PS5	47.5	1.195	1.189	0.4751	
15 minute summer	PS5	1.004	PS6	54.1	1.361	1.367	0.7426	
15 minute summer	PS6	1.005	Headwall 2	53.8	1.353	1.335	0.1183	
15 minute summer	Headwall 2	1.006	Headwall 1	59.7	1.501	3.439	0.5851	
15 minute summer	Headwall 1	1.007	PS7	39.1	0.984	0.423	0.1078	
15 minute summer	PS9	2.000	PS10	19.0	1.081	1.317	0.5021	
15 minute summer	PS10	2.001	PS15	29.1	0.733	0.732	0.4387	
15 minute summer	PS15	2.002	Headwall 4	31.0	0.780	0.767	0.0785	
15 minute winter	Headwall 4	2.003	Headwall 3	36.1	0.995	1.507	0.7537	
60 minute winter	Headwall 3	2.004	PS7	15.3	0.680	0.162	0.1041	
60 minute summer	PS16	3.000	PS17	5.5	1.133	0.195	0.0631	
15 minute summer	PS17	3.001	PS18	34.2	1.609	0.861	0.7567	

Results for 100 year +45% CC Critical Storm Duration. Lowest mass balance: 92.80%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
720 minute winter	PS18	720	8.692	0.617	7.4	102.9993	0.0000	SURCHARGED
720 minute winter	PS7	705	8.692	0.677	9.4	0.7656	0.0000	SURCHARGED
960 minute winter	Outfall	390	8.023	0.023	0.9	0.0000	0.0000	OK
Link Event (Velocity)	US Node	Link Node	DS Node	Outflow (l/s)	Velocity (m/s)	Flow/Cap	Link Vol (m³)	Discharge Vol (m³)
15 minute summer	PS18	3.002	PS7	-52.7	-1.451	-1.328	0.4076	
960 minute winter	PS7	1.008	Outfall	0.9	0.401	0.022	0.0055	48.6

Project **Lake Lane, Barnham**

Project ref **12188**

Date **Sep-24**

GTA C&T LTD ©

**Tank -Flotation Calculation**

<b>Tank ref:</b>	<b>Calc 1</b>		
Tank Area at base (m <sup>2</sup> )	216.000		
Ground Level (m AOD)	9.200		
Top GW level(m AOD)	8.600		
Top of Tank Level (m AOD)	8.700		
Base of Tank level(m AOD)	8.200		
Depth of Tank (m)	0.500		
Depth of water table above tank (m)	0.000		
Depth of Tank within Water table (m)	0.400		
Depth of cover over tank (m)	0.500		
Displacement depth below water table(m)	0.400		
Volume for buoyancy (m <sup>3</sup> )	86.400		
<b>Tank Buoyancy force (kN)</b>	847.6		
Total depth over tank (m)	0.500		
Fill soil downward force (kN)	1695.60		
<b>Downward anchor forces (kN)</b>	1695.60		
<b>Net Buoyancy Force</b>	848.02		
<b>Factor of safety</b>	2.0		

Obtain groundwater level from soil report

 Indicates field to be completed

9.81kN/m<sup>3</sup> for water. Positive figure denotes uplift force, negative figure denotes downward force

Note: If a negative figure is shown above for tank buoyancy then no ballast is required

Density of Dry soil = 1600 Kg/m<sup>3</sup> = 15.7kn/m<sup>3</sup> (Adjust if different backfill)

Negative figure denotes uplift force, positive figure denotes downward force  
minimum acceptable value: 1.1

Project **Lake Lane, Barnham**

Project ref **12188**

Date **Sep-24**

GTA C&T LTD ©

**Pond Flotation Calculation**

Pond	Calc 1		
Pond Area at base (m <sup>2</sup> )	33.600		
Pond Area at highest GW level (m <sup>2</sup> )	167.000		
Average Pond area (m <sup>2</sup> )	100.300		
Top GW level(m AOD)	8.600		
Pond base (m AOD)	7.985		
Depth GW- Base (m)	0.615		
Ballast thickness (m)	0.400		
Topsoil depth	0.150		
Overall depth (m)	1.165		
Volume for buoyancy (m <sup>3</sup> )	116.850		
<b>Buoyancy uplift (kN)</b>	1146.3		
Assumed dry (liner below ballast)			
Ballast construction depth (m)	0.400		
Ballast downward force (kN)	1249.18		
Topsoil depth (m)	0.150		
Topsoil downward force (kN))	79.13		
<b>Downward forces (kN)</b>	1324.28		
<b>Net Buoyancy Force</b>	177.99		
<b>Factor of safety</b>	1.2		

Calculate the area of the pond at the highest GW level  
average of area at highest GW level & area at base  
Obtain groundwater level from soil report

 Indicates field to be completed

Start with an assumed ballast depth, then adjust if FoS is less than 1.1

Bottom of ballast to top groundwater level


9.81kN/m<sup>3</sup> for water. Positive figure denotes uplift force, negative figure denotes downward force

Note: If a negative figure is shown above for pond buoyancy then no ballast is required

Unsaturated Clay = 1900Kg/m<sup>3</sup> or 18.64kN/m<sup>3</sup> - Saturated Clay = 2300Kg/m<sup>3</sup> or 22.56kN/m<sup>3</sup>(Engineeringtoolbox.com)

Density of Dry Topsoil = 1600 Kg/m<sup>3</sup> = 15.7kn/m<sup>3</sup>

Negative figure denotes uplift force, positive figure denotes downward force  
minimum acceptable value: 1.1



## Civil Engineering - Transport Planning - Flood Risk

GTA Civils & Transport, Maple House, 192-198 London Road, Burgess Hill, West Sussex, RH15 9RD

