

Project **Lake Lane, Barnham**

Project ref **12188**

Date **Sep-24**

GTA C&T LTD ©

Tank -Flotation Calculation

| Tank ref: | Calc 1 | | |
|-----------------------------------------|----------------|--|--|
| Tank Area at base (m2) | 216.000 | | |
| Ground Level (m AOD) | 9.200 | | |
| Top GW level(m AOD) | 8.600 | | |
| Top of Tank Level (m AOD) | 8.700 | | |
| Base of Tank level(m AOD) | 8.200 | | |
| Depth of Tank (m) | 0.500 | | |
| Depth of water table above tank (m) | 0.000 | | |
| Depth of Tank within Water table (m) | 0.400 | | |
| Depth of cover over tank (m) | 0.500 | | |
| Displacement depth below water table(m) | 0.400 | | |
| Volume for buoyancy (m ³) | 86.400 | | |
| Tank Buoyancy force (kN) | 847.6 | | |
| | | | |
| Total depth over tank (m) | 0.500 | | |
| Fill soil downward force (kN) | 1695.60 | | |
| Downward anchor forces (kN) | 1695.60 | | |
| Net Buoyancy Force | 848.02 | | |
| Factor of safety | 2.0 | | |
| OK | | | |

Obtain groundwater level from soil report

 Indicates field to be completed

9.81kN/m³ for water. Positive figure denotes uplift force, negative figure denotes downward force

Note: If a negative figure is shown above for tank buoyancy then no ballast is required

Density of Dry soil = 1600 Kg/m3 = 15.7kn/m3 (Adjust if different backfill)

Negative figure denotes uplift force, positive figure denotes downward force
minimum acceptable value: 1.1