

GROUND GAS AND GROUNDWATER MONITORING RESULTS



SITE/REF: Yapton						General Site comments			
DATE: 02/03/2020		1... of1...							
OPERATOR(S): RP									
Ambient Conditions:		Barometric Pressure (mb)	CH ₄ (%v/v)	CO ₂ (%v/v)	O ₂ (%v/v)		PID (ppm)		
Before Monitoring							EQUIPMENT		
After Monitoring									
Atmospheric Pressure Trend:									
Ground Conditions:									
Weather Conditions:							Instrument / Model Type	Serial Number	Comments
							Standard Dipmeter		

Ground Gas Note: "0" readings to be recorded as instrument detection limit

Borehole ID	Time	Flow (l/hr)	Relative Pressure (mb)	Steady CH ₄ (%v/v)	CO ₂ (%v/v)	O ₂ (%v/v)	Peak CH ₄ (%v/v)	% of Lower Explosive Limit	CO (ppm)	H ₂ S (ppm)	Balance (%)	PID (ppm)	Response Zone		Response Strata	Gas screening value CH ₄	Gas screening value CO ₂
													From (mbgl)	To (mbgl)			

Groundwater

Borehole ID	Standing Water Level (mbgl)	Installation Base Dip (mbgl)	Free Phase LNAPL Thickness (m)	Free Phase DNAPL Thickness (m)	Water Quality Indicators					Well Volume (l)	Purge Volume (l)	Comments (samples)
					Eh	EC	pH	DO	Temp			
WS101	2.53	4.94										
WS102	4.59	5.03										

Well volume (l) = (3.14 x (hole diameter (m)/2)² x (base dip (m) - standing water level (m)))x1000 (2l/m in 50mm well) Gas screening value = gas concentration (%) x gas flow rate (l/hr)

%v/v - Percentage volume by total volume; mbgl - metres below ground level; ppm - parts per million; mb - milibars; l/hr - litres per hour; wv - water vial; gb - 1l glass bottle; pb - 1l plastic bottle