

(C) JAMES BLAKE ASSOCIATES LTD 2020

NB DO NOT USE HYTEX FABRIC ON SLOPES GREATER THAN 1:4 WITHOUT THE USE OF GRAVEL BOARDS AT 1 - 1.5m CENTRES ALONG THE CONTOURS TO RETAIN THE GRAVEL.

N6: Hedges adjacent to level areas shall have the cultivated strip separated from gravel by a 1.3 m wide 75 x 25mm of ACQ treated timber stained with 2% coats of Sadolin® Classic colour 'Walnut' (dark brown wood stain) according to specification.

to 1.5m centres along the

text" from Hy-Lex U.K. Ltd. not
least, 20mm gravel, unless

G) Firm in and replace faces of fabric tightly around base of plant stems. ensure there is no soil what
so ever over the stem mulch. Peg as necessary.

H) Water plants with 20, plant for 10, sack and 10, plant for 3, or smaller stock using a fine spray
noze.

I) Spread coarse graded free-flowing large wood chip mulch" 50mm deep. Finished surface levels to
be 15mm below adjacent turf or paving.

*A list of James Blake Associates Approved Landscape Contractors is available on request.

The Black Barn, Hall Road, Lavenham, Suffolk, CO10 9QX
Tel: (01787) 248216 Fax: (01787) 247264
james@jba-landmarc.com www.jba-landmarc.com

Ar