

- This drawing is to be read in conjunction with all other Bright Plan Civils drawings, and with all relevant Architect's and Engineer's drawings and specification. Any discrepancies found are to be reported immediately to the Engineer.
- Bright Plan Civils accepts no responsibility for inaccuracies in data provided by third parties such as topographic surveys or Ordnance Survey mapping.
- Do not scale, work to figured dimensions only. All dimensions are in millimeters unless noted otherwise and all levels are in metres from the topographic survey datum.
- Any information given regarding existing underground services is given in good faith after consultation with the relevant authority, however accuracy is not certain. The main contractor is responsible for checking all information on site prior to work commencing and taking due care whilst undertaking the works.
- All dimensions to be checked on site. All details and dimensions relating to sub-contractors work must be checked and agreed between the sub-contractor or supplier and the general contractor.
- The electronic information from this drawing can not be guaranteed as dimensionally drawn exact. Figured dimensions must be used for setting out and detailing. Bright Plan Civils logos and company information must be removed from copies if information is re-used.



ADOPTABLE SURFACE WATER DRAINAGE	PRIVATE SURFACE WATER DRAINAGE	PRIVATE FOUL WATER DRAINAGE
PRECAST CONCRETE RING MANHOLE (1.5m DEPTH TO SOFFIT)	PRECAST CONCRETE RING MANHOLE (OVER 1.5m DEPTH TO SOFFIT, OF DENOTES CATCHPIT)	INSPECTION CHAMBER (MAX 1.2m DEPTH TO INVERT)
PROPOSED PUBLIC SURFACE WATER SEWER	450/600 ROAD GULLY	SHALLOW INSPECTION CHAMBER (MAX 0.6m DEPTH TO INVERT)
PROPOSED SURFACE WATER SEWER HEADWALL	INSPECTION CHAMBER (MAX 1.2m DEPTH TO INVERT, OF DENOTES CATCHPIT)	PRECAST CONCRETE RING MANHOLE (OVER 1.5m DEPTH TO SOFFIT)
ADOPTABLE FOUL WATER DRAINAGE	PRIVATE SURFACE WATER DRAINAGE	PRIVATE FOUL WATER DRAINAGE
PRECAST CONCRETE RING MANHOLE (1.5m DEPTH TO SOFFIT)	PERMEABLE PAVING (TANDED WITH CONNECTION TO SURFACE WATER DRAINAGE SYSTEM WITH FORMATION LEVELS)	PRIVATE FOUL WATER DRAINAGE
PROPOSED PUBLIC FOUL WATER SEWER	SURFACE WATER DIFFUSER UNIT AND INVERT LEVEL	
PROPOSED PUBLIC FOUL WATER PIPING MAIN	PERMEABLE PAVING (INFILTRATION WITH FORMATION LEVELS)	
HIGHWAY DRAINAGE		
PRECAST CONCRETE RING MANHOLE (1.5m DEPTH TO SOFFIT)		
450/600 ROAD GULLY		
HIGHWAY DRAINAGE		

