

DUAL HAZARDS


- In addition to the hazards/risks normally associated with the type of work detailed on this drawing, note the following:
1. Uncharted buried services. Contractor to use CAT prior to excavating.
 2. Working in live carriageway. Contractor to implement traffic management to ensure safety of the workforce and public.
 3. Working in live sewers. Contractor to ensure operatives are familiar with the dangers of working in live sewers.
 4. Excavations close to existing structures. Contractor to prepare method statement to ensure stability of existing structures.

It is assumed that all works will be carried out by a competent contractor working, where appropriate, to an approved risk assessment and method statement


BRIGHT PLAN CIVILS
Transport Planning and Infrastructure Design Consultants
2 West Barn, Norton Lane, Chichester, West Sussex PO20 3AF
Tel: 01243 210418
www.bpcivils.co.uk enquiries@bpcivils.co.uk

PIPE PASSING THROUGH A LINTELLED OPENING (Scale 1:20)

-
- 600
- 150 MAX.
- (Varies)



Depth of cover less than 0.6m under private gardens and 0.9m under private drives
(Scale 1:20)



Depth of cover greater than 0.6m under private gardens and 0.9m under private drives
(Scale 1:20)

Selected fill: free from stones larger than 40mm, lumps of clay over 100mm timber frozen material and vegetable matter.

Granular material: should conform to BS 882:1983 table 4 or BS 8301:1985


Appendix D. Compaction fraction > 0.3

'x' - Denotes external pipe diameter.



(Scale 1:20)

Depth to invert of less than 600mm.




(Not to Scale)



(Scale 1:20)

Depth to invert 1.25m (standard unit)
Silt Traps installed greater than single unit depth to be extended
using inspection chamber shaft units.



NOTE:
Polypipe products shall be used where possible for below ground drainage

(Not to Scale)

This plan complies with the Building Regulations 2002
Section 'H' - Drainage & Waste Disposal.