

- This drawing is to be read in conjunction with all other Bright Plan Civils drawings, and with all relevant Architect's and Engineer's drawings and specification. Any discrepancies found are to be reported immediately to the Engineer.
- Bright Plan Civils accepts no responsibility for inaccuracies in data provided by third parties such as topographic surveys or Ordnance Survey mapping.
- Do not scale, work to figured dimensions only. All dimensions are in millimeters unless noted otherwise and all levels are in metres from the topographic survey datum.
- Any information given regarding existing underground services is given in good faith after consultation with the relevant authority, however accuracy is not certain. The main contractor is responsible for checking all information on site prior to work commencing and taking due care whilst undertaking the works.
- All dimensions to be checked on site. All details and dimensions relating to sub-contractors work must be checked and agreed between the sub-contractor or supplier and the general contractor.
- The electronic information from this drawing can not be guaranteed as dimensionally drawn exact. Figured dimensions must be used for setting out and detailing. Bright Plan Civils logos and company information must be removed from copies if information is re-used.



ADOPTABLE SURFACE WATER DRAINAGE	PRIVATE SURFACE WATER DRAINAGE	PRIVATE FOUL WATER DRAINAGE
PRECAST CONCRETE RING MANHOLE (ø1.5m DEPTH TO SOFTH)	PRECAST CONCRETE RING MANHOLE (OVER 1.5m DEPTH TO SOFTH OF DRENCHES CATCHES)	INSPECTION CHAMBER (MAX 1.2m DEPTH TO INVERT)
PROPOSED PUBLIC SURFACE WATER SEWER	400/600 ROAD GULLY	SHALLOW INSPECTION CHAMBER (MAX 0.5m DEPTH TO INVERT)
PROPOSED SURFACE WATER SEWER HEADWALL	INSPECTION CHAMBER (MAX 0.6m DEPTH TO INVERT)	PRECAST CONCRETE RING MANHOLE (OVER 1.5m DEPTH TO SOFTH)
ADOPTABLE FOUL WATER DRAINAGE	PRIVATE SURFACE WATER DRAINAGE	PRIVATE FOUL WATER DRAINAGE
PRECAST CONCRETE RING MANHOLE (ø1.5m DEPTH TO SOFTH)	INSPECTION CHAMBER (MAX 1.2m DEPTH TO INVERT OF DRENCHES CATCHES)	PRIVATE FOUL WATER DRAINAGE
PROPOSED PUBLIC FOUL WATER SEWER	PRIVATE SURFACE WATER DRAINAGE	PERMEABLE PAVING (TANKED WITH CONNECTION TO SURFACE WATER DRAINAGE SYSTEM WITH FORMATION LEVELS)
PROPOSED PUBLIC FOUL WATER SEWER HEADWALL	0.00 SURFACE WATER DIFFUSER UNIT AND INVERT LEVEL	PERMEABLE PAVING (INFILTRATION) WITH FORMATION LEVELS
HIGHWAY DRAINAGE		
PRECAST CONCRETE RING MANHOLE (ø1.5m DEPTH TO SOFTH)		
400/600 ROAD GULLY		
HIGHWAY DRAINAGE		

C	Adjustment to Plot 91 SW drainage	15/03/23
B	Plot 70 and 71 diffuser locations updated	01/03/23
A	Drawing key added	11/10/22
REV.	Amendments	Date



BRIGHT PLAN CIVILS
Transport Planning and Infrastructure Design Consultants
2 West Barn, Norton Lane, Chichester, West Sussex PO20 3AF
Tel: 01243 210418
www.bpcivils.co.uk enquiries@bpcivils.co.uk

Drawing Status FOR APPROVAL

Client THAKEHAM

Project BILSHAM ROAD
YAPTONDrawing Title PROPOSED PERMEABLE PAVING
FORMATION LEVELS AND DIFFUSERS

Scale 1:500 Date Feb 22 Drawn By LDF Checked By MJA

Drawing No. D1956-13-301 Rev. C